



# AMERICAN ROCKWOOL MANUFACTURING

Corporate Offices: 1316 Village Creek Drive, Suite 600 Plano, Texas 75093

Plant: 440 Jackrabbit Road / P.O. Box C Nolanville, TX 76559

## Open Blow Attic Application - 30 lb Bag

R-Value*	Thickness - Minimum (")	Thickness - Settled (")	Maximum Net SF Coverage	Weight / SF lbs.	Bags / 1000 SF
11	3.2	3.2	65.5	0.5	15.3
13	3.8	3.8	55.4	0.6	18.1
19	5.6	5.6	37.9	0.8	26.4
22	6.5	6.5	32.7	1.0	30.6
26	7.6	7.6	27.7	1.1	36.1
30	8.8	8.8	24.0	1.3	41.7
33	9.7	9.7	21.8	1.5	45.8
38	11.2	11.2	19.0	1.7	52.8
49	14.4	14.4	14.7	2.2	68.0

\*R-Value is a measure of insulating ability at a mean temperature of 75°F. "R" means resistance to heat flow. The higher the "R" value, the greater the insulation power.

## Side Wall Application - 30 lb. Bag

	R-Value 2.5# Density	R-Value 4# Density	Coverage/Bag 2.5# Density	Coverage/Bag 4# Density	Bags / 1000 SF @ 2.5#	Bags / 1000 SF @ 4#
2 x 4 Wood Stud	14	15	41.1	25.7	24.3	38.9
2 x 4 Metal Stud	14	15	39.7	24.8	25.2	40.3
2 x 6 Wood Stud	21.5	23	26.2	16.4	38.2	61.0
2 x 6 Metal Stud	22	23.5	25.6	16	39.1	62.5

The contents of one bag installed in open wall areas by pneumatic equipment with Premium Plus Wall Adhesive provides insulation resistance "R" values at the weight and coverages shown above.

Builder's and Applicator's Statement and Signature

This is to certify that the insulation has been installed in conformance with the requirements indicated on this card to provide a value of:

"R" = \_\_\_\_\_ using \_\_\_\_\_ bags of insulation to cover \_\_\_\_\_ sq. ft. of area.

Date:

Dealer

Builders Signature

Date

Applicator

Applicators Signature

For more information contact technical support at: (877) 247-5970

or by email: [techservice@americanrockwool.com](mailto:techservice@americanrockwool.com)